



SAFETY DATA SHEET

Metal Gray Epoxy Seam Sealer/Adhesive - Hardener

Page: 1

Revision: 11/12/2021

Supersedes Revision: 05/12/2014

1. Product and Company Identification

Product Code: CMG7 (H)
Product Name: Metal Gray Epoxy Seam Sealer/Adhesive - Hardener
Company Name: Crest Industries, Inc. **Phone Number:**
1337 King Road (734)479-4141
Trenton, MI 48183
Web site address: crestauto.com
Emergency Contact: Chemtel (800)255-3924
International Calls (813)248-0585

2. Hazards Identification

Acute Toxicity: Oral, Category 4
Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2A
Skin Sensitization, Category 1



GHS Signal Word: **Warning**

GHS Hazard Phrases: H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.

GHS Precautionary Phrases: P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P330 - Rinse mouth.
P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+313 - If eye irritation persists, get medical advice/attention.
P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal Phrases: P501 - Dispose of contents/container in accordance with local/regional/national and international regulations.

Inhalation: May be harmful if inhaled. Material may be irritating to mucous membranes and upper respiratory tract.

Skin Contact: Causes skin irritation.

Eye Contact: Causes severe eye irritation.

Ingestion: Harmful if swallowed.

Skin Absorption: May be harmful if absorbed through the skin.



SAFETY DATA SHEET

Metal Gray Epoxy Seam Sealer/Adhesive - Hardener

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
NA	Mercaptan Terminated Polymer	85.00 - 95.00 %
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	1.000 - 10.00 %
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	1.000 - 5.000 %

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation:	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Get medical attention/advice if you feel unwell.
In Case of Skin Contact:	In case of contact, immediately wash skin with soap and copious amounts of water. Get medical aid if irritation develops and persists.
In Case of Eye Contact:	In case of contact, immediately flush eyes with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.
In Case of Ingestion:	If swallowed, wash out mouth with water provided person is conscious. Call a physician.

5. Fire Fighting Measures

Flash Pt:	> 350 C (662 F) Method Used: Estimate
Explosive Limits:	LEL: UEL:
Autoignition Pt:	
Suitable Extinguishing Media:	Use water spray, dry chemical, carbon dioxide, or appropriate foam.
Fire Fighting Instructions:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Flammable Properties and

Hazards:

Hazardous Combustion

Products:

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:	Absorb on sand or vermiculite and place in closed containers for disposal.
---	--

7. Handling and Storage

Precautions To Be Taken in Handling:	Avoid contact with eyes, skin, and clothing. Do not ingest or inhale.
Precautions To Be Taken in Storing:	Store in a dry place.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
NA	Mercaptan Terminated Polymer			
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol			
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica			



SAFETY DATA SHEET

Metal Gray Epoxy Seam Sealer/Adhesive - Hardener

Respiratory Equipment (Specify Type):	Always use a NIOSH or European Standard EN 149 approved respirator when necessary.
Eye Protection:	Chemical safety goggles.
Protective Gloves:	Hand: Compatible chemical-resistant gloves. Eyes:
Other Protective Clothing:	
Engineering Controls (Ventilation etc.):	Use with adequate ventilation.
Work/Hygienic/Maintenance Practices:	Wash thoroughly after handling.

9. Physical and Chemical Properties

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	White. sulfurous odor.
pH:	
Melting Point:	
Boiling Point:	
Flash Pt:	> 350 C (662 F) Method Used: Estimate
Evaporation Rate:	
Flammability (solid, gas):	
Explosive Limits:	LEL: UEL:
Vapor Pressure (vs. Air or mm Hg):	
Vapor Density (vs. Air = 1):	> 1
Specific Gravity (Water = 1):	
Density:	1.02 G/CM3
Solubility in Water:	miscable
Octanol/Water Partition Coefficient:	
Autoignition Pt:	
Decomposition Temperature:	
Viscosity:	

10. Stability and Reactivity

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	flames and sparks.
Incompatibility - Materials To Avoid:	Strong oxidizing agents.
Hazardous Decomposition or Byproducts:	Hazardous Decomposition Products: silicon oxides. Carbon monoxide, Carbon dioxide, Nitrogen oxides.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	



SAFETY DATA SHEET

Metal Gray Epoxy Seam Sealer/Adhesive - Hardener

Revision: 11/12/2021
Supersedes Revision: 05/12/2014

11. Toxicological Information

Toxicological Information:

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
NA	Mercaptan Terminated Polymer	n.a.	n.a.	n.a.	n.a.
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	n.a.	n.a.	n.a.	n.a.
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

13. Disposal Considerations

Waste Disposal Method: APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION.
Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):**DOT Proper Shipping Name:** Not Regulated.**DOT Hazard Class:****UN/NA Number:****LAND TRANSPORT (Canadian TDG):****TDG Shipping Name:****UN Number:****Hazard Class:****TDG Classification:****MARINE TRANSPORT (IMDG/IMO):****IMDG/IMO Shipping Name:** Aviation regulated liquid, n.o.s.**UN Number:** 3334**Packing Group:** III**Hazard Class:** 9 - CLASS 9**IMDG MFAG Number:****IMDG EMS Page:****AIR TRANSPORT (ICAO/IATA):****ICAO/IATA Shipping Name:** Aviation regulated liquid, n.o.s. (Polymercaptan)**UN Number:****Packing Group:****Hazard Class:**

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
NA	Mercaptan Terminated Polymer	No	No	No
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	No	No	No
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	No	No	No

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Explosive	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Acute toxicity (any route of exposure)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Flammable (gases, aerosols, liquid, or solid)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Skin Corrosion or Irritation
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Oxidizer (liquid, solid or gas)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Serious eye damage or eye irritation
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Self-reactive	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Respiratory or Skin Sensitization
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Pyrophoric (liquid or solid)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Germ cell mutagenicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Pyrophoric gas	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Carcinogenicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Self-heating	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Reproductive toxicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Organic peroxide	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Specific target organ toxicity (single or repeated exposure)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Corrosive to metal	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Aspiration Hazard



Metal Gray Epoxy Seam Sealer/Adhesive -

Revision: 11/12/2021

Hardener

Supersedes Revision: 05/12/2014

Yes No Gas under pressure (compressed gas)

Yes No Simple Asphyxiant

Yes No In contact with water emits flammable gas

Yes No (Health) Hazard Not Otherwise Classified (HNOC)

Yes No Combustible Dust

Yes No (Physical) Hazard Not Otherwise Classified (HNOC)

CAS #	Hazardous Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
NA	Mercaptan Terminated Polymer	No	No	No
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	No	No	Yes
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	No	No	Yes

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
NA	Mercaptan Terminated Polymer	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8A, 8A PAIR; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

16. Other Information

Revision Date: 11/12/2021 **Previous revision:** 05/12/2014

Additional Information About This Product:

Company Policy or Disclaimer: The information contained in this SDS is believed to be accurate and reliable as of the date indicated. Crest Industries, Inc. assumes no legal responsibility and makes no representation, warranty or guarantee, expressed or implied, as to the completeness or accuracy of the information. It is offered solely for your consideration, investigation and verification. The user is ultimately responsible for the safe use of the material in accordance with applicable federal, state, provincial and local laws and regulations.



Metal Gray Epoxy Seam Sealer/Adhesive - Resin

Revision: 11/12/2021

Supersedes Revision: 05/12/2014

1. Product and Company Identification

Product Code: CMG7 (R)

Product Name: Metal Gray Epoxy Seam Sealer/Adhesive - Resin

Company Name: Crest Industries, Inc. **Phone Number:**
 1337 King Road (734)479-4141
 Trenton, MI 48183

Web site address: crestauto.com

Emergency Contact: Chemtel (800)255-3924
 International Calls (813)248-0585

2. Hazards Identification

Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2A
Skin Sensitization, Category 1



GHS Signal Word: **Warning**

GHS Hazard Phrases: H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.

GHS Precautionary Phrases: P261 - Avoid breathing dust/fume.
 P264 - Wash hands thoroughly after handling.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear gloves/protective clothing/eye protection.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.
 P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
 P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+313 - If eye irritation persists, get medical advice/attention.
 P362 - Take off contaminated clothing and wash before re-use.

GHS Storage and Disposal Phrases: P501 - Dispose of contents/container in accordance with local/regional/national and international regulations.

Potential Health Effects (Acute and Chronic): Chronic:

Inhalation: Causes chemical burns to the respiratory tract. May be harmful if inhaled. Material is irritating to mucous membranes and upper respiratory tract.

Skin Contact: Harmful if absorbed through the skin. Causes skin irritation.

Eye Contact: Causes eye irritation.

Ingestion: Harmful if swallowed. Causes gastrointestinal tract burns.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
25068-38-6	Bisphenol-a based epoxy resin	70.00 - 80.00 %
7631-86-9	Silica	1.000 - 10.00 %



Metal Gray Epoxy Seam Sealer/Adhesive - Resin

Revision: 11/12/2021

Supersedes Revision: 05/12/2014

4. First Aid Measures**Emergency and First Aid****Procedures:****In Case of Inhalation:**

If inhaled, remove to fresh air. Get medical attention/advice if you feel unwell.

In Case of Skin Contact:

In case of contact, immediately wash skin with soap and copious amounts of water. Get medical aid if irritation develops and persists.

In Case of Eye Contact:

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid if irritation or symptoms occur.

In Case of Ingestion:

If swallowed, wash out mouth with water provided person is conscious. Call a physician.

Signs and Symptoms Of Exposure:

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

CHRONIC EXPOSURE - CARCINOGEN.

Species: Rat.

Route of Application: Inhalation, Dose: 5 MG/M3 Exposure Time: 7H/90W Frequency: I.

Specific Developmental Abnormalities: Tumorigenic: Carcinogenic by RTECS criteria.

Blood: Leukemia.

Route of Application: Intraperitoneal Dose: 50 MG/KG

Result: Tumorigenic: Equivocal tumorigenic agent by RTECS criteria.

Gastrointestinal: Tumors.

Route of Application: Implant, Dose: 200 MG/KG

Result: Tumorigenic: Neoplastic by RTECS criteria. Tumorigenic: Tumors at site of application.

Species: Rabbit.

Route of Application: Intraperitoneal Dose: 25 MG/KG

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria.

Species: Hamster.

Route of Application: Intraperitoneal Dose: 400 MG/KG

Route of Application: Intratracheal, Dose: 125 MG/KG

Exposure Time: 5W Frequency: I. Lungs, Thorax, or Respiration: Tumors.

Species: Mouse.

Route of Application: Implant, Dose: 1600 MG/KG

Kidney, Ureter, Bladder: Tumors.

Route of Application: Intrapleural, Dose: 100 MG/KG. CHRONIC EXPOSURE - MUTAGEN.

Species: Human, Dose: 10 MG/L Cell Type: fibroblast

Mutation test: Other mutation test systems.

Species: Hamster, Dose: 2 UG/CM2, Cell Type: lung.

Mutation test: Micronucleus test.

Species: Hamster, Dose: 10 MG/L, Cell Type: ovary.

Note to Physician:

Treat symptomatically and supportively.



SAFETY DATA SHEET

Metal Gray Epoxy Seam Sealer/Adhesive - Resin

5. Fire Fighting Measures

Flash Pt: > 149 C (> 300 F) Method Used: Estimate

Explosive Limits: LEL: UEL:

Autoignition Pt: NA

Suitable Extinguishing Media: For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, use water spray, fog, or alcohol-resistant foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Combustible liquid.
Specific Hazard(s):

Flammable Properties and

Hazards:

Hazardous Combustion

Products:

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Use proper personal protective equipment as indicated in Section 8.
Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container.

7. Handling and Storage

Precautions To Be Taken in Handling: Do not ingest or inhale. Avoid contact with eyes, skin, and clothing.

Precautions To Be Taken in Storing: Store in a cool, dry place.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
25068-38-6	Bisphenol-a based epoxy resin			
7631-86-9	Silica			

Respiratory Equipment (Specify Type): Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Use adequate ventilation to keep airborne concentrations low.

Work/Hygienic/Maintenance Practices: Wash thoroughly after handling.



Metal Gray Epoxy Seam Sealer/Adhesive - Resin

Revision: 11/12/2021

Supersedes Revision: 05/12/2014

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Gray.
sweetish odor.

pH:

Melting Point: NA

Boiling Point:

Flash Pt: > 149 C (> 300 F) Method Used: Estimate

Evaporation Rate:

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or mm Hg):

Vapor Density (vs. Air = 1): > 1

Specific Gravity (Water = 1):

Density: ~ 1.03 G/CM3

Solubility in Water:

Octanol/Water Partition Coefficient:

Autoignition Pt: NA

Decomposition Temperature:

Viscosity:

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability: Incompatible materials, Excess heat.

Incompatibility - Materials To Avoid: Strong oxidizing agents.

Hazardous Decomposition or Byproducts: Carbon monoxide, Hazardous Decomposition Products: silicon oxides.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions:

**Metal Gray Epoxy Seam Sealer/Adhesive - Resin**

Revision: 11/12/2021

Supersedes Revision: 05/12/2014

11. Toxicological Information

Toxicological Information: Epidemiology: No data available.
 Teratogenicity: No data available.
 Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies:
Carcinogenicity/Other Information: CAS# 2238-07-5: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
25068-38-6	Bisphenol-a based epoxy resin	n.a.	n.a.	n.a.	n.a.
7631-86-9	Silica	Known	3	n.a.	n.a.

12. Ecological Information

General Ecological Information: Environmental: No information available.
 Physical: No information available.
 Other: Do not empty into drains.

13. Disposal Considerations

Waste Disposal Method: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.
 RCRA P-Series: None listed.
 RCRA U-Series: None listed. APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

14. Transport Information**LAND TRANSPORT (US DOT):**

DOT Proper Shipping Name: Not Regulated.

DOT Hazard Class:

UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: No information available.

UN Number:

Hazard Class:

TDG Classification:

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Environmentally hazardous substances, liquid, n.o.s.

UN Number: 3082

Packing Group:

III

Hazard Class: 9 - CLASS 9

IMDG MFAG Number:

IMDG EMS Page:

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Environmentally hazardous substances, liquid, n.o.s. (Bisphenol A Epoxy Resin)

UN Number: 3082

Packing Group:

III

Hazard Class: 9 - CLASS 9



Metal Gray Epoxy Seam Sealer/Adhesive - Resin

Revision: 11/12/2021

Supersedes Revision: 05/12/2014

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
7631-86-9	Silica	No	No	No

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Explosive	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Acute toxicity (any route of exposure)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Flammable (gases, aerosols, liquid, or solid)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Skin Corrosion or Irritation
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Oxidizer (liquid, solid or gas)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Serious eye damage or eye irritation
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Self-reactive	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	Respiratory or Skin Sensitization
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Pyrophoric (liquid or solid)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Germ cell mutagenicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Pyrophoric gas	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Carcinogenicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Self-heating	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Reproductive toxicity
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Organic peroxide	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Specific target organ toxicity (single or repeated exposure)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Corrosive to metal	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Aspiration Hazard
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Gas under pressure (compressed gas)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Simple Asphyxiant
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	In contact with water emits flammable gas	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	(Health) Hazard Not Otherwise Classified (HNOC)
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Combustible Dust		
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	(Physical) Hazard Not Otherwise Classified (HNOC)		

CAS #	Hazardous Components (Chemical Name)	Canadian NPRI	Canadian Toxic	Canadian DSL
25068-38-6	Bisphenol-a based epoxy resin	No	No	Yes
7631-86-9	Silica	No	No	Yes

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
25068-38-6	Bisphenol-a based epoxy resin	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
7631-86-9	Silica	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC: Cat. IIIa/b, Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: No

16. Other Information

Revision Date: 11/12/2021 **Previous revision:** 05/12/2014

Additional Information About

This Product:

Company Policy or

Disclaimer:

The information contained in this SDS is believed to be accurate and reliable as of the date indicated. Crest Industries, Inc. assumes no legal responsibility and makes no representation, warranty or guarantee, expressed or implied, as to the completeness or accuracy of the information. It is offered solely for your consideration, investigation and verification. The user is ultimately responsible for the safe use of the material in accordance with applicable federal, state, provincial and local laws and regulations.